

TM6 SERIES MONO CONTACT BIMETALLIC THERMOSTAT

200 BAR Rated

TM6 temperature switches permit opening or closing of an electric circuit in order to reach a fixed temperature value.

Article no.	Fix Set Switching °C	Max Pressure BAR
TM64	40	200
TM65	50	200
TM66	60	200
TM67	70	200
TM68	80	200
TM69	90	200
TM69.0	100	200
TM69.1	110	200



TM6
90° Swinging connector and
incorporated seal fluid side



Ordering Code

TM6	5	A	1
IDENT	PRESET VALUE 4 = 40°C 5 = 50°C ETC	PRESET A = NORMALLY OPEN C = NORMALLY CLOSED	CONNECTION 1 = 1/2" BSP 2 = 3/8" BSP

Technical Features

Body	Brass
Connection	1/2" BSP Male (3/8" BSP on request)
Mounting	Any orientation
Temp. Range	-20 to +120°C
Frequency	20 Cycles/min
Accuracy	±3.5°C
Fixed Hysteresis	12°C
Weight	0.17kg

Electrical Features M2 (DIN PLUG)

Electrical Connection	DIN 43650
Weatherproof Rating	IP65
Max. Contact Load	220v (10A) 120v (15A)

Dimensions

